



ANLY CONTROLLER

EC4-1 EXCHANGE RELAY



CHARACTERISTIC :

- Switching Mode Power Supply for 100~240V AC/DC operation
- Up to 4 loads can be individually selected via DIP switch
- Up to 11 load combinations are possible (Please see the table below)
- Load 1 & 2 are C/O contacts; Load 3 & 4 are N.O. contacts
- Change Time between loads can be adjusted from 0.2 to 10 sec
- S1, Load exchange signal can be rising-edge or falling edge
- S2, All-On signal can force all selected loads to start sequentially
- Load Memory can let users chose to either resume the running load or to always start from Load 1 after a power reset
- a power reset is required for setting changes to take effect


SPECIFICATION :

Operating voltage	AC/DC(V): 100 ~ 240
Allowable operating voltage range	85~110% of rated operating voltage
Rated frequency	50 / 60 Hz
Contact rating	250VAC 5A (resistive load)
Reset time	MAX 0.1S
Power consumption	Approx. 2.3VA
Life	Mechanical: 5,000,000 times Electrical: 100,000 times
Ambient temperature	-10 ~ +50°C
Ambient humidity	MAX 85%RH
Weight	Approx. 150g


LOAD COMBINATIONS :

Groups	2 Loads						3 Loads				4 Loads
	1	2	3	4	5	6	7	8	9	10	11
Load 1	○	○	○				○	○	○		○
Load 2	○			○	○		○	○		○	○
Load 3		○		○		○	○		○	○	○
Load 4			○		○	○		○	○	○	○


CONNECTION :



TIMING CHART :



DIMENSIONS : (mm)



ANLY ELECTRONICS CO., LTD.

<http://www.anly.com.tw>

TAIWAN MAIN OFFICE : ANLY ELECTRONICS CO., LTD.

No.19, Lane 202, Fushou St., Xinzhuang Dist., New Taipei City 242, Taiwan
 TEL: +886-2-2996-3202 FAX: +886-2-2996-2017

MALAYSIA BRANCH : JUSTY ELECTRONICS (M) SDN, BHD.

No.1, Jalan 6/89B, Kawasan Perindustrian Triseqi, Batu 3 1/2 Off Jalan Sungei Besi, 57100 Kuala Lumpur, Malaysia
 TEL: +60-3-7983-5758 FAX: +60-3-7981-5052

HONG KONG BRANCH : ANLY ELECTRONICS (HK) LTD.

Flat K, 13/F, Edward Mansion, 141 Prince Edward Road W., Kowloon, Hong Kong
 TEL: +852-2397-2505 FAX: +852-2397-6080

SHANGHAI BRANCH : ANLY TECHNOLOGY (WUXI) CO., LTD.

Room 13G, No.831, Xinzha Rd., Jingan District, Shanghai, China 200041
 TEL: +86-21-6218-3300 FAX: +86-21-6217-5911