



ANLY TIMER

APT-6S / APT-6SB WEEKLY PROGRAMMABLE TIMER



CHARACTERISTIC :

- Weekly programmable timer
- Also can be used as 24-hour timer
- 8 different timing settings per day
- 15 different weekly combinations (See chart below)
- Built-in Lithium battery prevent power outage up to one year
- Crystal oscillator for extreme accuracy
- Backlit LCD for easy viewing*
- UL, C-UL recognized and CE certified

Note: "*" indicates applicable to APT-6SB only

SPECIFICATION :

Operating voltage	AC/DC(V): 12~48 AC/DC(V): 100~240
Allowable operating voltage range	85~110% of rated operating voltage
Rated frequency	50 / 60 Hz
Contact rating	240VAC 7A(N.O.) resistive load 240VAC 5A(N.C.) resistive load
Indicator operating	ON - Green, OFF - Red
Power consumption	Approx. 3.3VA
Life	Mechanical: 5,000,000 times Electrical: 100,000 times
Ambient temperature	-10 ~ +50°C (without condensation & freezing)
Ambient humidity	MAX 65% RH (without condensation)
Altitude	MAX 2000m
Weight	Approx. 150g

15 weekly combinations chart :


	SUN	MON	TUE	WED	THU	FRI	SAT
1		⊙					
2			⊙				
3				⊙			
4					⊙		
5						⊙	
6							⊙
7	⊙						
8		⊙	⊙	⊙	⊙	⊙	

	SUN	MON	TUE	WED	THU	FRI	SAT
9		⊙	⊙	⊙	⊙	⊙	⊙
10	⊙						⊙
11	⊙	⊙	⊙	⊙	⊙	⊙	⊙
12		⊙	⊙	⊙			
13					⊙	⊙	⊙
14		⊙		⊙		⊙	
15			⊙		⊙		⊙


CONNECTION :

When a time switch and load power supply are separate

N type(Surface Mounting)




Y type(Flush Mounting)




When a time switch and load power supply are the same

N type(Surface Mounting)




Y type(Flush Mounting)




DIMENSIONS : (mm)

N type(Surface Mounting):



Y type(Flush Mounting): Using Y70 Adapter



Tolerance:±0.1

ANLY ELECTRONICS CO., LTD.

<http://www.anly.com.tw>

TAIWAN MAIN OFFICE : ANLY ELECTRONICS CO., LTD.

No.19, Lane 202, Fushou St., Xinzhuang Dist., New Taipei City 242, Taiwan
TEL: +886-2-2996-3202 FAX: +886-2-2996-2017

MALAYSIA BRANCH : JUSTY ELECTRONICS (M) SDN, BHD.

No.1, Jalan 6/89B, Kawasan Perindustrian Triseqi, Batu 3 1/2 Off Jalan Sungei Besi, 57100 Kuala Lumpur, Malaysia
TEL: +60-3-7983-5758 FAX: +60-3-7981-5052

HONG KONG BRANCH : ANLY ELECTRONICS (HK) LTD.

Flat K, 13/F, Edward Mansion, 141 Prince Edward Road W., Kowloon, Hong Kong
TEL: +852-2397-2505 FAX: +852-2397-6080

SHANGHAI BRANCH : ANLY TECHNOLOGY (WUXI) CO., LTD.

Room 13G, No.831, Xinzha Rd., Jingan District, Shanghai, China 200041
TEL: +86-21-6218-3300 FAX: +86-21-6217-5911