



ANLY TIMER

H3B MULTI-RANGE ANALOGUE TIMER



CHARACTERISTIC :

- 5 (A, B, C, D, E) timing series available
- Each timing series has 4 time ranges, selectable via DIP switch
- A/B Mode selectable with a slide switch. A Mode for 2C Delayed output contacts. B Mode for 2C Inst.+Delayed output contacts.
- UL, C-UL recognized and CE certified

SPECIFICATION :

Operating voltage	DC(V): 12, 24 AC(V): 100-120 or 200-240
Allowable operating voltage range	85~110% of rated operating voltage
Rated frequency	50 / 60 Hz
Contact rating	250VAC 5A (resistive load)
Reset time	MAX 0.1S
Power consumption	DC 12V: 0.85W , DC 24V: 1.1W AC120V: 3.5VA , AC240V: 6.5VA
Life	Mechanical: 5,000,000 times Electrical: 100,000 times
Ambient temperature	-10 ~ +50°C (without condensation & freezing)
Ambient humidity	MAX 85% RH (without condensation)
Altitude	MAX 2000m
Weight	Approx. 105g

TYPE SELECTION :

Type	Time range			
H3B-A	1S	10S	1M	10M
H3B-B	3S	30S	3M	30M
H3B-C	6S	60S	6M	60M
H3B-D	1M	10M	1H	10H
H3B-E	3M	30M	3H	30H

